190AR1 Series Flow Gauge Regulators

Model 190AR1 Series Flow Gauge Regulators are designed for light duty MIG applications to provide accurate regulation of gas flow, and reliable performance in commercial, industrial and laboratory applications.

- 2" flow gauge for easy reading
- Body machined from class "A" brass
- Chrome plated housing cap
- Internal pressure relief design
- Sintered bronze inlet filter
- Plastic adjustment knob for smooth "easy touch" flow settings
- 0 50 SCFH argon (Ar) flow
- Weight: 1 lb 15 oz
- UL listed



190AR1

Model Number	Gas Service	Flow Capacity (SCFH)	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection
190AR1-50	ARGON, AR/CO ₂ MIX	0-50	NONE	2", 50SCFH	CGA580	5/8" - 18RH(F), .032 ORIFICE
190AR1-50-B						3/16" BARB, .032 ORIFICE
190AR1-50-P						5/32" PUSH-IN-TUBE, .032 ORIFICE

1 psi = 0.00689 MPa = 6.895 kPa = 0.06895 bar = 0.07 kgf / cm2, 1 scfh = 0.0283 m3/h = 0.472 LPM

190 Series Flow Gauge Regulators

Model 190 Series "MIG METER" Flow Gauge Regulators are designed for MIG & TIG applications to provide accurate regulation of gas flow. They are ideal for commercial, industrial and laboratory applications.

- 2" gauges for easy reading
- Forged brass body and housing cap
- Chrome plated housing cap
- Internal pressure relief design
- Accurate measurement of gas flow up to 50 SCFH
- Choice of inlet connections for argon (CGA 580) or carbon dioxide (CGA 320)
- Plastic adjustment knob for smooth "easy touch" flow settings
- Weight: 2 lbs 3 oz
- UL listed



190AR

Model Number	Gas Service	Flow Capacity (SCFH)	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection
190AR-50	ARGON, AR/CO ₂ MIX	0-50	2", 4000PSI	2", 50SCFH	CGA580	5/8" - 18RH(F), .032 ORIFICE
190AR-50-B						3/16" BARB, .032 ORIFICE
190AR-50-P						5/32" PUSH-IN-TUBE, .032 ORIFICE
190CD-45	CARBON DIOXIDE	0-45	2", 4000PSI	2", 50SCFH	CGA320	5/8" - 18RH(F), .032 ORIFICE

1 psi = 0.00689 MPa = 6.895 kPa = 0.06895 bar = 0.07 kgf / cm2, 1 scfh = 0.0283 m3/h = 0.472 LPM